

G 4 X product line	Part-No.	Description	Power connection	Pump motor	Star wheel motor	Mixing tube	Mixing shaft	Deflector	Rotor/Stator	Outlet pressure flange	Water pressure booster pump	Control unit	Idle running control	Compressor	Rubber cover for compressor	PVC dust protection cover for water armature	Star wheel capacity	Spraying gun	Mortar hose	Water / Air hose	Wheels	Power cable	Additional accessory	Water flow meter	Tool box with tool kit	Transport locking device
230V	00 26 81 43	G 4 X FC 230V with water pressure booster pump 0,37/230V	230V, 1Ph, 50Hz	4 kW, 400 rpm, 2 stage gear Inclination switch	0,3 kW, 12 rpm	Steel mixing tube with D-flange	Mixing shaft G 4 straight	no	SD 6-3 slimline	25mm male-part Mortar pressure gauge firmly integrated	SL 0,37kW	Large control box housing Frequency converter Infinitely adjustable revolution	no	Delta 2 with pressure switch off	no	no	55 l/min	Smartline 25mm Spraying cap 14mm 200mm long straight version	Rondo 25mm 10m long hydraulically fitted	11m 1/2" Ewo/Geka	2 Castors 2 Double lockable castors	25m 3 x 32 A adapter coupling Schuko/CEE	Cleaning shaft Mixing tube cleaner Cleaner coupling Manual	150-1500 l/h	yes	no
230V	00 40 21 18	G 4 X FC 230V without water pressure booster pump	230V, 1Ph, 50Hz	4 kW, 400 rpm, 2 stage gear Inclination switch	0,3 kW, 12 rpm	Steel mixing tube with D-flange	Mixing shaft G 4 straight	no	SD 6-3 slimline	25mm male-part Mortar pressure gauge firmly integrated	no	Large control box housing Frequency converter Infinitely adjustable revolution	no	Delta 2 with pressure switch off	no	no	55 l/min	Smartline 25mm Spraying cap 14mm 200mm long straight version	Rondo 25mm 10m long hydraulically fitted	11m 1/2" Ewo/Geka	2 Castors 2 Double lockable castors	25m 3 x 32 A adapter coupling Schuko/CEE	Cleaning shaft Mixing tube cleaner Cleaner coupling Manual	150-1500 l/h	yes	no
230V	00 41 42 34	G 4 X FC 230V with water pressure booster pump 0,37/230V	230V, 1Ph, 50Hz	4 kW, 400 rpm, 2 stage gear Inclination switch	0,3 kW, 12 rpm	Steel mixing tube with D-flange	Mixing shaft G 4 straight	no	SD 6-3 slimline	25mm male-part Mortar pressure gauge firmly integrated	SL 0,37kW	Large control box housing Frequency converter Infinitely adjustable revolution	no	Delta 2 with pressure switch off	no	no	55 l/min	Standard 25mm Spraying cap 14mm 600mm long 30° angled turnable coupling aluminum	Rondo 25mm 10m long hydraulically fitted	11m 1/2" Ewo/Geka	2 Castors 2 Double lockable castors	25m 3 x 32 A adapter coupling Schuko/CEE	Cleaning shaft Mixing tube cleaner Cleaner coupling Manual	150-1500 l/h	yes	no
230V 1Ph / 400V 3Ph	00 26 06 21	G 4 X FC 230/400V with water pressure booster pump 0,37/230V	230V, 1Ph, 50Hz or 400V, 3Ph, 50Hz	5,5 kW, 385 rpm, 2 stage gear Inclination switch	0,3 kW, 12 rpm	Rubber mixing tube with interchangeable flange	Mixing shaft G 4 straight	yes	SD 6-3 slimline	35mm female-part Mortar pressure gauge firmly integrated	SL 0,37kW	Large control box housing Frequency converter Infinitely adjustable revolution at 230V operation	no	Delta 2 with pressure switch off	yes	no	55 l/min	Standard 25mm Spraying cap 14mm 200mm long straight version turnable coupling aluminum	Rondo 25mm 10m long hydraulically fitted	11m 1/2" Ewo/Geka	2 Castors 2 Double lockable castors	25m 3 x 32 A adapter coupling Schuko/CEE	Cleaning shaft Mixing tube cleaner Cleaner coupling Manual	150-1500 l/h	yes	yes
230V 1Ph / 400V 3Ph	00 42 34 08	G 4 X FC 230/400V without water pressure booster pump	230V, 1Ph, 50Hz or 400V, 3Ph, 50Hz	5,5 kW, 385 rpm, 2 stage gear Inclination switch	0,3 kW, 12 rpm	Rubber mixing tube with interchangeable flange	Mixing shaft G 4 straight	yes	SD 6-3 slimline	35mm female-part Mortar pressure gauge firmly integrated	no	Large control box housing Frequency converter Infinitely adjustable revolution at 230V operation	no	Delta 2 with pressure switch off	yes	no	55 l/min	Standard 25mm Spraying cap 14mm 200mm long straight version turnable coupling aluminum	Rondo 25mm 10m long hydraulically fitted	11m 1/2" Ewo/Geka	2 Castors 2 Double lockable castors	25m 3 x 32 A adapter coupling Schuko/CEE	Cleaning shaft Mixing tube cleaner Cleaner coupling Manual	150-1500 l/h	yes	yes
SMART	00 25 73 59	G 4 X smart with water pressure booster pump 0,37/400V	400V, 3Ph, 50Hz	5,5 kW, 385 rpm, 2 stage gear Inclination switch	0,75 kW, 28 rpm	Steel mixing tube with D-flange	Mixing shaft G 4 straight	no	D6-3 maintenance free orange	25mm male-part Mortar pressure gauge firmly integrated	SL 0,37kW	Small control box housing Transformer with automatic fuse and motor protection switch	no	LK 250 with pressure switch off	no	no	55 l/min	Smartline 25mm Spraying cap 14mm 200mm long straight version	Rondo 25mm 10m long hydraulically fitted	11m 1/2" Ewo/Geka	3 Castors 1 Double lockable castors	no	Cleaning shaft Mixing tube cleaner Cleaner coupling Manual	100-1000 l/h	yes	no
SMART	00 26 06 22	G 4 X smart without water pressure booster pump	400V, 3Ph, 50Hz	5,5 kW, 385 rpm, 2 stage gear Inclination switch	0,75 kW, 28 rpm	Steel mixing tube with D-flange	Mixing shaft G 4 straight	no	D6-3 maintenance free orange	25mm male-part Mortar pressure gauge firmly integrated	no	Small control box housing Transformer with automatic fuse and motor protection switch	no	LK 250 with pressure switch off	no	no	55 l/min	Smartline 25mm Spraying cap 14mm 200mm long straight version	Rondo 25mm 10m long hydraulically fitted	11m 1/2" Ewo/Geka	3 Castors 1 Double lockable castors	no	Cleaning shaft Mixing tube cleaner Cleaner coupling Manual	100-1000 l/h	yes	no
SMART	00 41 42 31	G 4 X smart without water pressure booster pump and K2 N	400V, 3Ph, 50Hz	5,5 kW, 385 rpm, 2 stage gear Inclination switch	0,75 kW, 28 rpm	Steel mixing tube with D-flange	Mixing shaft G 4 straight	no	D6-3 maintenance free orange	25mm male-part Mortar pressure gauge firmly integrated	no	Small control box housing Transformer with automatic fuse and motor protection switch	no	K 2 N with pressure switch off	no	no	55 l/min	Smartline 25mm Spraying cap 14mm 200mm long straight version	Rondo 25mm 10m long hydraulically fitted	11m 1/2" Ewo/Geka	3 Castors 1 Double lockable castors	no	Cleaning shaft Mixing tube cleaner Cleaner coupling Manual	100-1000 l/h	yes	no
SMART	00 41 42 38	G 4 X smart without water pressure booster pump - geothermal energy	400V, 3Ph, 50Hz	5,5 kW, 385 rpm, 2 stage gear Inclination switch	0,75 kW, 28 rpm	Steel mixing tube with D-flange	Mixing shaft G 4 straight	no	D6-2 maintenance free	25mm male-part Mortar pressure gauge firmly integrated	no	Small control box housing Transformer with automatic fuse and motor protection switch	no	no	no	no	55 l/min	no	no	no	3 Castors 1 Double lockable castors	no	Cleaning shaft Mixing tube cleaner Cleaner coupling Manual	100-1000 l/h	yes	no
STANDARD	00 23 84 74	G 4 X without water pressure booster pump	400V, 3Ph, 50Hz	5,5 kW, 385 rpm, 2 stage gear Inclination switch	0,75 kW, 28 rpm	Steel mixing tube with interchangeable flange	Mixing shaft G 4 straight	yes	Twister D6-3	35mm female-part Mortar pressure gauge firmly integrated	no	Large control box housing with phase monitor with working hour meter Transformer with automatic fuse and motor protection switch	no	K 2 N with pressure switch off	yes	no	85 l/min	Standard 25mm Spraying cap 14mm 200mm long straight version turnable coupling aluminum	Rondo 25mm 10m long hydraulically fitted	11m 1/2" Ewo/Geka	2 Castors 2 Double lockable castors	no	Cleaning shaft Mixing tube cleaner Cleaner coupling Manual	150-1500 l/h	yes	yes
STANDARD	00 40 21 68	G 4 X with water pressure booster pump AV1000	400V, 3Ph, 50Hz	5,5 kW, 385 rpm, 2 stage gear Inclination switch	0,75 kW, 28 rpm	Steel mixing tube with interchangeable flange	Mixing shaft G 4 straight	yes	Twister D6-3	35mm female-part Mortar pressure gauge firmly integrated	AV 1000	Large control box housing with phase monitor with working hour meter Transformer with automatic fuse and motor protection switch	no	K 2 N with pressure switch off	yes	no	85 l/min	Standard 25mm Spraying cap 14mm 200mm long straight version turnable coupling aluminum	Rondo 25mm 10m long hydraulically fitted	11m 1/2" Ewo/Geka	2 Castors 2 Double lockable castors	no	Cleaning shaft Mixing tube cleaner Cleaner coupling Manual	150-1500 l/h	yes	yes
STANDARD	00 41 41 94	G 4 X with water pressure booster pump 0,37 kW/400V	400V, 3Ph, 50Hz	5,5 kW, 385 rpm, 2 stage gear Inclination switch	0,75 kW, 28 rpm	Steel mixing tube with interchangeable flange	Mixing shaft G 4 straight	yes	Twister D6-3	35mm female-part Mortar pressure gauge firmly integrated	SL 0,37kW	Large control box housing with phase monitor with working hour meter Transformer with automatic fuse and motor protection switch	no	K 2 N with pressure switch off	yes	no	85 l/min	Standard 25mm Spraying cap 14mm 200mm long straight version turnable coupling aluminum	Rondo 25mm 10m long hydraulically fitted	11m 1/2" Ewo/Geka	2 Castors 2 Double lockable castors	no	Cleaning shaft Mixing tube cleaner Cleaner coupling Manual	150-1500 l/h	yes	yes
STANDARD	00 41 42 24	G 4 X with rubber mixing tube	400V, 3Ph, 50Hz	5,5 kW, 385 rpm, 2 stage gear Inclination switch	0,75 kW, 28 rpm	Rubber mixing tube with interchangeable flange	Mixing shaft G 4 straight	yes	Twister D6-3	35mm female-part Mortar pressure gauge firmly integrated	no	Large control box housing with phase monitor with working hour meter Transformer with automatic fuse and motor protection switch	no	K 2 N with pressure switch off	yes	no	85 l/min	Standard 25mm Spraying cap 14mm 200mm long straight version turnable coupling aluminum	Rondo 25mm 10m long hydraulically fitted	11m 1/2" Ewo/Geka	2 Castors 2 Double lockable castors	no	Cleaning shaft Mixing tube cleaner Cleaner coupling Manual	150-1500 l/h	yes	yes
STANDARD	00 42 38 48	G 4 X with rubber mixing tube and water pressure booster pump AV1000	400V, 3Ph, 50Hz	5,5 kW, 385 rpm, 2 stage gear Inclination switch	0,75 kW, 28 rpm	Rubber mixing tube with interchangeable flange	Mixing shaft G 4 straight	yes	Twister D6-3	35mm female-part Mortar pressure gauge firmly integrated	AV 1000	Large control box housing with phase monitor with working hour meter Transformer with automatic fuse and motor protection switch	no	K 2 N with pressure switch off	yes	no	85 l/min	Standard 25mm Spraying cap 14mm 200mm long straight version turnable coupling aluminum	Rondo 25mm 10m long hydraulically fitted	11m 1/2" Ewo/Geka	2 Castors 2 Double lockable castors	no	Cleaning shaft Mixing tube cleaner Cleaner coupling Manual	150-1500 l/h	yes	yes
STANDARD	00 42 51 00	G 4 X Floor screed	400V, 3Ph, 50Hz	5,5 kW, 385 rpm, 2 stage gear Inclination switch	0,75 kW, 28 rpm	Steel mixing tube with interchangeable flange	Mixing shaft G 4/G 5 for trowel plaster	yes	R8-1.5 with clamp	35mm female-part	AV 1000	Large control box housing with phase monitor with working hour meter Transformer with automatic fuse and motor protection switch	no	no	no	no	85 l/min	no	RONDO 35 mm 20 m long male coupling hydraulic (four hoses)	no	2 Castors 2 Double lockable castors	no	Cleaning shaft Mixing tube cleaner Cleaner coupling Manual Rotomix Mortar pressure gauge 35mm	250-2500 l/h	yes	yes
SUPER	00 41 41 71	G 4 X Super	400V, 3Ph, 50Hz	5,5 kW, 385 rpm, 2 stage gear Inclination switch	0,75 kW, 28 rpm	Rubber mixing tube with interchangeable flange	Mixing shaft G 4 straight	yes	Twister D6-3	35mm female-part Mortar pressure gauge firmly integrated	AV 1000	Large control box housing with phase monitor with working hour meter Transformer with automatic fuse and motor protection switch Idle running control Automatic direction of rotation Control lamp for water pressure (ready for GPS)	Level sensor inside material hopper	K 2 N with pressure switch off	yes	no	85 l/min	Standard 25mm Spraying cap 14mm 200mm long straight version turnable coupling aluminum	Rondo 25mm 15m long hydraulically fitted	15m 1/2" Ewo/Geka	2 Castors 2 Double lockable castors	no	Cleaning shaft Mixing tube cleaner Cleaner coupling Manual	150-1500 l/h	yes	yes
XL	00 40 67 95	G 4 X XL	400V, 3Ph, 50Hz	7,5 kW, 400 rpm, 2 stage gear Inclination switch	0,75 kW, 28 rpm	Rubber mixing tube with interchangeable flange	Mixing shaft G 4 straight	yes	D6-4 maintenance free	35mm female-part Mortar pressure gauge firmly integrated	AV 1000	Large control box housing with phase monitor with working hour meter Transformer with automatic fuse and motor protection switch Idle running control Automatic direction of rotation Control lamp for water pressure (ready for GPS)	Level sensor inside material hopper	K 2 N with pressure switch off	yes	yes	85 l/min	Standard 25mm Spraying cap 14mm 200mm long straight version turnable coupling aluminum	Rondo 25mm 10m long hydraulically fitted	11m 1/2" Ewo/Geka	2 Castors 2 Double lockable castors	no	Cleaning shaft Mixing tube cleaner Cleaner coupling Rotor wrench Manual	150-1500 l/h	yes	yes