





# PFT BOLERO

Two running directions, two driving speeds – many applications:
Mixing, pumping, spraying, all of this is done with the small mixing pump of PFT.

### **Functional description**

The handy PFT BOLERO is a combination of mixing, pumping and spraying machine. If material, which is roughed up intensely, shall be processed, the new PFT BOLERO is the perfect machine.

In clockwise mode of the mixing shaft the material is mixed continuously. In anticlockwise mode the pumping machine is connected and pumps the ready-mixed material to the place of use.

## Fields of application

Many materials which need to be roughed up intensely or rather need a source time such as

- Reinforcement, adhesive mortars
- ► Fire protection mortars
- Mortar of various components
- Betonite
- ► Structure and acoustic plaster
- Leveling compound and interior primer

#### Advantages at a glance


- Cost-effective, versatile solution for small construction sites
- Combination of mixing, pumping and spraying pump with clockwise and anti-clockwise operation
- Stipulated mixing and mortar source times can be precisely adhered.
- Mixing errors are virtually eliminated
- For spraying with air assistance you may use a PFT compressor
- Light-weight, easy to transport
- Two revs
- Mortar pressure gauge integrated
- Big wheels matched to specific site conditions
- ► Safety switch





All rights and technical changes reserved. We provide guarantee as far as faultless and proper finishing of our machines is concerned. Figures given in relation to output, equipment and performance are based on experience and can vary in case of changing circumstances. Furthermore, the instructions of the material/mortar manufacturers must be observed. Alterations, reprints and photomechanical reproductions, even in extracts, require the permission of Knauf PFT GmbH & Co. KG.

PFT BOLERO-GB/06.11/PFT



#### **Knauf PFT**

Technical Hotline:

- +49 9323 31-1818
- Phone +49 9323 31-760
- Fax +49 9323 31-770
- info@pft-iphofen.de
- www.pft.eu

## Technical data

## **PFT BOLERO**

Part no.	00 23 12 13
Drive	1.9 kW geared motor
Speed	90 or 181 rpm at 50 Hz
Power connection	400 V, 50 Hz, three-phases
Fuse protection	3 x 16 A
Rotor/Stator	D4-2 standard equipment
Pump capactiy*	6 or 12 l/min
Conveying distance*	up to 30 m
Conveying height*	up to 15 m
Conveying pressure*	max. 25 bar
Grain size*	max. 4 mm

#### **Dimensions and weights**

Filling height	950 mm
Hopper content	681
Length/width/height	800/700/1,500 mm
Chassis with material hopper / control unit	64 kg
Motor with protection grille	42 kg
Agitator with freewheel	6 kg
Total weight	112 kg

<sup>\*</sup> Guidelines depending on conveying height, pump condition and version, pump unit, mortar quality, composition and consistency.

The respective directives and recommendations of the material producer are to be observed.









## **Basic equipment**

Mixing pump PFT BOLERO with

- Gear motor 1,9 kW
- Control unit
- Material hopper with protection grille
- Agitator with freewheel
- Pump unit D4-2 with clamp
- Mortar pressure gauge
- Pump shaft
- Pressure flange
- Remote control cable 25 m cpl.
- Tool bag
- Operating instructions

## **Accessories**

Power cable  $5 \times 2.5 \, \text{mm}^2$ ,  $25 \, \text{m}$ , CEE cpl.  $16 \, \text{A}$  Part no.  $20 \, 42 \, 33 \, 60$ 

RONDO 25 mm, 15 m,

with hydraulically fitted couplings Part no. 00 02 11 01

Spanga hall Ø 30 mm

Sponge ball Ø 30 mm, packing unit = 20 pieces Part no. 20 21 05 00

ZARGOMAT- and gluing gun with 15 m cable, 25 female part Part no. 20 19 50 00

#### Knauf PFT GmbH & Co. KG

P.O. Box 60 97343 Iphofen Einersheimer Straße 53 97346 Iphofen Germany Knauf Gips

Dry construction- and Soil-Systems

Knauf AMF Ceiling Systems

Knauf Bauprodukte Pro Solutions at Home Knauf Gips / Marmorit Plaster and Facade Systems

Knauf Dämmstoffe Polystyrol Insulating Material

Marbos Mortar Systems in Civil Engineering Knauf Insulation Insulating Material: Rock Wool, Glass Wool and Wood Wool

Knauf Integral Gypsum Fibre Technology for Soil, Wall and Ceiling Knauf Perlite AQUAPANEL® Cement Boards, Perlit

Sakret Bausysteme
Dry Mortar for
New Build and Renovation